

# MASTER LEDtube InstantFit HF

### MASTER LEDtube HF 1500mm UO 26W830 T8

The Philips MASTER LEDtube integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance which cannot be distinguished from traditional fluorescent. The MASTER LEDtube Performance is the ideal solution for customers which have higher light requirements and the want to maximize value over lifetime.(need the longest lifetime). Full energy savings and TCO benefits.

### Product data

### General Information

Cap-Base G13 [ Medium Bi-Pin Fluorescent] Main Application Industrial 50000 h Nominal Lifetime (Nom) Switching Cycle 50000X B50L70 50000

### • Light Technical

830 [ CCT of 3000K] Color Code Beam Angle (Nom) 160 3400 lm Luminous Flux (Nom) 3400 lm Luminous Flux (Rated) (Nom) 160° Rated Beam Angle 3000 K Correlated Color Temperature (Nom) Color Consistency 6 steps Color Rendering 83 Index (Nom) Llmf At End Of 70 % Nominal Lifetime (Nom)

### • Operating and Electrical

Input Frequency 25000/80000 Hz Power (Rated) 26 W (Nom) Lamp Current (Nom) 400 mA 0.5 s Starting Time (Max) Warm Up Time To 0.1 s60% Light (Max) Power Factor (Min) 0.9 50-100 V Voltage (Nom)

### • Temperature

45 °C T-Ambient (Max) T-Ambient (Min) -20 °C 65 °C T-Storage (Max) T-Storage (Min) -40 °C 45 °C T-Case Maximum (Nom)

### · Controls and Dimming

Dimmable No

### · Mechanical and Housing

Product Length 1500 mm

### • Approval and Application

**Energy Saving** Yes Product Suitable For Accent No Lighting Energy Efficiency Label (EEL)

Approval Marks

CE marking

KEMA Keur certificate RoHS compliance VDE marking 31 kWh

Energy Consumption kWh/1000 h

• Product Data

871869655288900 Full product code



# MASTER LEDtube InstantFit HF

MASTER LEDtube HF 1500mm UO 26W830 T8 8718696552889 Order product name

929001211602

Numerator - Quan-


EAN/UPC - Product Order code

tity Per Pack

Numerator - Packs 10

per outer box Material Nr. (12NC) Net Weight (Piece) 929001211602 0.450 kg

### Dimensional drawing




### TLED 50-100V 26W-58W 3700lm 3000K G13 ND

Product	D1	D2	A1	A2	A3
MASTER LEDtube HF 1500mm UO 26W830 T8	25.68 mm	28 mm	1500.0 mm	1507.1 mm	1514.2 mm

# Photometric data

MASTER LEDtube InstantFit HF

## MASTER LEDtube InstantFit HF





© 2016 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.