Wings

| CRI 85
7415



Technische Daten	
Installationsposition	Wand
Installationsumgebung	Indoor
Lichtquelle	LED
Optik	General Lighting
Light emission direction	upward
Lampenleistung	19 W
Lichtstrom (Lichtquelle)	1380 lm
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tonalità	3000 K
Farbwiedergabeindex	85 Ra
AC/DC	AC
Isolierklasse	1
IP	IP40
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
ETL	Nein
Einschließlich Driver	Ja
Induzione	Nein
Notbeleuchtung	Nein
Motion sensor	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Nettogewicht	0.785 Kg

Oberfläche Gehäuse	
Material	Aluminium
Farbe	Schwarz RAL 9005
Bearbeitungstyp	Lackierung

Oberfläche Diffusor	
Material	PC
Bearbeitungstyp	Sandstrahlen

Wings

| CRI 85
7415

Single emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 120 topled LEDs with CCT of 3000 K and a CRI 85; the source luminous flux is 1380 lm, with a 72.6 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of aluminium and features a black ral 9005 finish, processed by means of coating; the diffuser is made of PC with a sandblasting treatment. The ingress protection degree is IP40; the total weight is of 0.785 kg. The power supply driver is included in the delivery.

The total absorbed power is 19 W.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	68 %
Lichtstrom (Lichtquelle)	1380 lm
Leuchten Lichtstrom	944 lm
Consumption	15 W
Leuchten Lichtausbeute	62 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	85 Ra

UGR	
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20
UGR transversal	< 19
UGR axial	< 16

OPTICAL	
Light distribution simmetry	Symmetrical 2
Ottica C0/C180	104°
Ottica C90/C270	97°