

PRODUCT DATASHEET

ORBIS Sparkle 600 38 W 827-865 Remote-CCT

ORBIS Sparkle | LED ceiling luminaires with sparkling effect



AREAS OF APPLICATION

- For indoor use only
- Decorative domestic lighting
- Ceiling and wall surface mounting

PRODUCT BENEFITS

- Very homogenous light
- Easy and quick installation

PRODUCT FEATURES

- Ceiling luminaire with advanced LED technology
- Circular light emission



TECHNICAL DATA


Electrical data

Nominal wattage	38.00 W
Operating mode	Integrated LED driver
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	2800 K
Color rendering index Ra	>80
Light color (designation)	Warm White/Cool White/Daylight
Luminous flux	3600 lm

Dimensions & weight



Diameter	600.0 mm
Height	120.0 mm
Product weight	1600.00 g

Colors & materials

Body material	Metal
Housing color	White
Product color	White

Additional product data

Mounting type	Surface
Mounting location	Ceiling

Capabilities

Dimmable	Yes
-----------------	-----

Type of connection	Terminal, 3-Pole (L, N, PE)
---------------------------	-----------------------------

Certificates & standards

Protection class	I
Type of protection	IP20

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075042216	ORBIS Sparkle 600 38 W 827-865 Remote-CCT	Shipping carton box 6	1137 mm x 665 mm x 670 mm	506.59 dm ³	26740.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.